

12.A: Review Questions

Complete as directed.

Fill in the Blanks:

1. Employees working along, at, above or near wall openings where the outside bottom edge of the wall openings is feet or more above lower levels must have fall protection provided.
2. The Fall Protection Standard sets up a uniform threshold of _____ feet for determining when fall protection is required.
3. The top height of the guardrail shall be _____ inches, plus or as a minus 3 inches.
4. Safety net systems must be installed as close as practical to the working surface and in no case more than _____ feet below such level.
5. Where no mechanical equipment is being used, warning lines must be located at least _____ feet from the roof edge.
6. Guardrails must be capable the standing a _____ pound downward force applied within _____ inches of the top rail at any point along the top edge.
7. Covers for floor openings must be marked with the word _____ or _____ or shall be color-coded to provide warning of the hazard.
8. The attachment point for a body harness, used for fall protection, shall be located where?

True or False: (Circle the Correct Answer)

1. Several types of activities covered by the standard can be performed without fall protection provided the employer can demonstrate the fall protection is infeasible or creates a great hazard by its use. T or F
2. If no other fall protection system has been implemented the employer must have a safety monitoring system. T or F

This page titled [12.A: Review Questions](#) is shared under a [CC BY 4.0](#) license and was authored, remixed, and/or curated by [Kimberly Mosley \(ASCCC Open Educational Resources Initiative \(OERI\)\)](#).

- [11.A: Review Questions](#) by [Kimberly Mosley](#) is licensed [CC BY 4.0](#).