

LibreTexts

A Physics Formulary

Johan Wevers

This text is disseminated via the Open Education Resource (OER) LibreTexts Project (<https://LibreTexts.org>) and like the hundreds of other texts available within this powerful platform, it is freely available for reading, printing and "consuming." Most, but not all, pages in the library have licenses that may allow individuals to make changes, save, and print this book. Carefully consult the applicable license(s) before pursuing such effects.

Instructors can adopt existing LibreTexts texts or Remix them to quickly build course-specific resources to meet the needs of their students. Unlike traditional textbooks, LibreTexts' web based origins allow powerful integration of advanced features and new technologies to support learning.



The LibreTexts mission is to unite students, faculty and scholars in a cooperative effort to develop an easy-to-use online platform for the construction, customization, and dissemination of OER content to reduce the burdens of unreasonable textbook costs to our students and society. The LibreTexts project is a multi-institutional collaborative venture to develop the next generation of open-access texts to improve postsecondary education at all levels of higher learning by developing an Open Access Resource environment. The project currently consists of 14 independently operating and interconnected libraries that are constantly being optimized by students, faculty, and outside experts to supplant conventional paper-based books. These free textbook alternatives are organized within a central environment that is both vertically (from advance to basic level) and horizontally (across different fields) integrated.

The LibreTexts libraries are Powered by [NICE CXOne](#) and are supported by the Department of Education Open Textbook Pilot Project, the UC Davis Office of the Provost, the UC Davis Library, the California State University Affordable Learning Solutions Program, and Merlot. This material is based upon work supported by the National Science Foundation under Grant No. 1246120, 1525057, and 1413739.

Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation nor the US Department of Education.

Have questions or comments? For information about adoptions or adaptations contact info@LibreTexts.org. More information on our activities can be found via Facebook (<https://facebook.com/Libretexts>), Twitter (<https://twitter.com/libretexts>), or our blog (<http://Blog.Libretexts.org>).

This text was compiled on 04/15/2025

TABLE OF CONTENTS

[Licensing](#)

[9.1: Physics Formulas \(Wevers\)](#)

- [Licensing](#)
- [9.1.1: Mechanics](#)
- [9.1.2: Oscillations](#)
- [9.1.3: Waves](#)
- [9.1.4: Physical Constants, Units, Del Operator](#)
 - [9.1.4.1: Physical Constants](#)
 - [9.1.4.2: Prefixes for Powers of 10](#)
 - [9.1.4.3: SI Units](#)
 - [9.1.4.4: The Del-operator](#)
- [Index](#)
- [Glossary](#)
- [Glossary](#)
- [Detailed Licensing](#)

[Index](#)

[Glossary](#)

[Glossary](#)

[Detailed Licensing](#)

Licensing

A detailed breakdown of this resource's licensing can be found in [Back Matter/Detailed Licensing](#).

9.1.1: Mechanics

Point-kinetics in a fixed coordinate system

Definitions

The position \vec{r} , the velocity \vec{v} and the acceleration \vec{a} are defined by: $\vec{r} = (x, y, z)$, $\vec{v} = (\dot{x}, \dot{y}, \dot{z})$, $\vec{a} = (\ddot{x}, \ddot{y}, \ddot{z})$. The following holds:

$$s(t) = s_0 + \int |\vec{v}(t)| dt; \quad \vec{r}(t) = \vec{r}_0 + \int \vec{v}(t) dt; \quad \vec{v}(t) = \vec{v}_0 + \int \vec{a}(t) dt \quad (9.1.1.1)$$

When the acceleration is constant this gives: $v(t) = v_0 + at$ and $s(t) = s_0 + v_0 t + \frac{1}{2} at^2$.

For the unit vectors in a direction \perp to the orbit \vec{e}_t and parallel to it \vec{e}_n :

$$\vec{e}_t = \frac{\vec{v}}{|\vec{v}|} = \frac{d\vec{r}}{ds} \quad \dot{\vec{e}}_t = \frac{v}{\rho} \vec{e}_n; \quad \vec{e}_n = \frac{\dot{\vec{e}}_t}{|\dot{\vec{e}}_t|} \quad (9.1.1.2)$$

For the curvature k and the radius of curvature ρ :

$$\vec{k} = \frac{d\vec{e}_t}{ds} = \frac{d^2\vec{r}}{ds^2} = \left| \frac{d\varphi}{ds} \right|; \quad \rho = \frac{1}{|k|} \quad (9.1.1.3)$$

Polar coordinates

Polar coordinates are defined by: $x = r \cos(\theta)$, $y = r \sin(\theta)$. So, for the unit coordinate vectors: $\dot{\vec{e}}_r = \dot{\theta} \vec{e}_\theta$, $\dot{\vec{e}}_\theta = -\dot{\theta} \vec{e}_r$.

The velocity and the acceleration are derived from:

$$\vec{r} = r \vec{e}_r, \quad \vec{v} = \dot{r} \vec{e}_r + r \dot{\theta} \vec{e}_\theta, \quad \vec{a} = (\ddot{r} - r \dot{\theta}^2) \vec{e}_r + (2\dot{r} \dot{\theta} + r \ddot{\theta}) \vec{e}_\theta \quad (9.1.1.4)$$

.

Relative motion

For the motion of a point D w.r.t. a point Q: $\vec{r}_D = \vec{r}_Q + \frac{\vec{\omega} \times \vec{v}_Q}{\omega^2}$ with $\vec{QD} = \vec{r}_D - \vec{r}_Q$ and $\omega = \dot{\theta}$.

Further a prime on a symbol $\alpha = \dot{\theta}$ means that the quantity is defined in a moving system of coordinates. In a moving system: $\vec{v} = \vec{v}_Q + \vec{v}' + \vec{\omega} \times \vec{r}'$ and $\vec{a} = \vec{a}_Q + \vec{a}' + \dot{\vec{\omega}} \times \vec{r}' + 2\vec{\omega} \times \vec{v}' + \vec{\omega} \times (\vec{\omega} \times \vec{r}')$ with $\vec{\omega} \times (\vec{\omega} \times \vec{r}') = -\omega^2 \vec{r}'_n$.

Point-dynamics in a fixed coordinate system

Force, (angular) momentum and energy

Newton's 2nd law connects the force on an object and the resulting acceleration of the object where the *momentum* is given by $\vec{p} = m\vec{v}$:

$$\vec{F}(\vec{r}, \vec{v}, t) = \frac{d\vec{p}}{dt} = \frac{d(m\vec{v})}{dt} = m \frac{d\vec{v}}{dt} + \vec{v} \frac{dm}{dt} \stackrel{m=\text{const}}{=} m\vec{a} \quad (9.1.1.5)$$

Newton's 3rd law is given by: $\vec{F}_{\text{action}} = -\vec{F}_{\text{reaction}}$.

For the power P : $P = \dot{W} = \vec{F} \cdot \vec{v}$. For the total energy W , the kinetic energy T and the potential energy U : $W = T + U$; $\dot{T} = -\dot{U}$ with $T = \frac{1}{2} mv^2$.

The kick \vec{S} is given by: $\vec{S} = \Delta\vec{p} = \int \vec{F} dt$

The work A , delivered by a force, is $A = \int_1^2 \vec{F} \cdot d\vec{s} = \int_1^2 F \cos(\alpha) ds$

The torque $\vec{\tau}$ is related to the angular momentum \vec{L} : $\vec{\tau} = \dot{\vec{L}} = \vec{r} \times \dot{\vec{F}}$; and $\vec{L} = \vec{r} \times \vec{p} = m\vec{v} \times \vec{r}$, $|\vec{L}| = mr^2\omega$. The following equation is valid:

$$\tau = -\frac{\partial U}{\partial \theta} \quad (9.1.1.6)$$

Hence, the conditions for a mechanical equilibrium are: $\sum \vec{F}_i = 0$ and $\sum \vec{\tau}_i = 0$.

The *force of friction* is usually proportional to the force perpendicular to the surface, except when the motion starts, when a threshold has to be overcome: $F_{\text{fric}} = f \cdot F_{\text{norm}} \cdot \vec{e}_t$.

Conservative force fields

A conservative force can be written as the gradient of a potential: $\vec{F}_{\text{cons}} = -\vec{\nabla}U$. From this follows that $\nabla \times \vec{F} = \vec{0}$. For such a force field also:

$$\oint \vec{F} \cdot d\vec{s} = 0 \Rightarrow U = U_0 - \int_{r_0}^{r_1} \vec{F} \cdot d\vec{s} \quad (9.1.1.7)$$

So the work delivered by a conservative force field depends not on the trajectory covered but only on the starting and ending points of the motion.

Gravitation

The *Newtonian law of gravitation* is (in GRT one also uses κ instead of G):

$$\vec{F}_g = -G \frac{m_1 m_2}{r^2} \vec{e}_r \quad (9.1.1.8)$$

The gravitational potential is then given by $V = -Gm/r$. From *Gauss' law* it then follows: $\nabla^2 V = 4\pi G\rho$.

Orbital equations

If $V = V(r)$ one can derive from the equations of *Lagrange* for ϕ the conservation of angular momentum:

$$\frac{\partial \mathcal{L}}{\partial \phi} = \frac{\partial V}{\partial \phi} = 0 \Rightarrow \frac{d}{dt}(mr^2\dot{\phi}) = 0 \Rightarrow L_z = mr^2\dot{\phi} = \text{constant} \quad (9.1.1.9)$$

For the radial position as a function of time it can be found that:

$$\left(\frac{dr}{dt}\right)^2 = \frac{2(W-V)}{m} - \frac{L^2}{m^2 r^2} \quad (9.1.1.10)$$

The angular equation is then:

$$\phi - \phi_0 = \int_0^r \left[\frac{mr^2}{L} \sqrt{\frac{2(W-V)}{m} - \frac{L^2}{m^2 r^2}} \right]^{-1} dr \stackrel{r=r_{\text{field}}}{=} \arccos\left(1 + \frac{\frac{1}{r} - \frac{1}{r_0}}{\frac{1}{r_0} + km/L_z^2}\right) \quad (9.1.1.11)$$

If $F = F(r)$: $L = \text{constant}$, if F is conservative: $W = \text{constant}$, if $\vec{F} \perp \vec{v}$ then $\Delta T = 0$ and $U = 0$.

Kepler's orbital equations

In a force field $F = kr^{-2}$, the orbits are conic sections with the origin of the force in one of the foci (*Kepler's 1st law*). The equation of the orbit is:

$$r(\theta) = \frac{\ell}{1 + \varepsilon \cos(\theta - \theta_0)}, \text{ or } x^2 + y^2 = (\ell - \varepsilon x)^2 \quad (9.1.1.12)$$

with

$$\ell = \frac{L^2}{G\mu^2 M_{\text{tot}}}; \quad \varepsilon^2 = 1 + \frac{2WL^2}{G^2\mu^3 M_{\text{tot}}^2} = 1 - \frac{\ell}{a}; \quad a = \frac{\ell}{1 - \varepsilon^2} = \frac{k}{2W} \quad (9.1.1.13)$$

a is half the length of the long axis of the elliptical orbit in case the orbit is closed. Half the length of the short axis is $b = \sqrt{a\ell}$. ε is the *excentricity* of the orbit. Orbits with an equal ε are of equal shape. Now, five types of orbits are possible:

1. $k < 0$ and $\varepsilon = 0$: a circle.
2. $k < 0$ and $0 < \varepsilon < 1$: an ellipse.
3. $k < 0$ and $\varepsilon = 1$: a parabola.
4. $k < 0$ and $\varepsilon > 1$: a hyperbola, curved towards the centre of force.
5. $k > 0$ and $\varepsilon > 1$: a hyperbola, curved away from the centre of force.

Other combinations are not possible: the total energy in a repulsive force field is always positive so $\varepsilon > 1$.

If the surface between the orbit covered between t_1 and t_2 and the focus C around which the planet moves is $A(t_1, t_2)$, Kepler's 2nd law is

$$A(t_1, t_2) = \frac{L_C}{2m} (t_2 - t_1) \quad (9.1.1.14)$$

Kepler's 3rd law is, with T the period and M_{tot} the total mass of the system is:

$$\frac{T^2}{a^3} = \frac{4\pi^2}{GM_{\text{tot}}} \quad (9.1.1.15)$$

The virial theorem

The virial theorem for one particle is:

$$\langle m\vec{v} \cdot \vec{r} \rangle = 0 \Rightarrow \langle T \rangle = -\frac{1}{2} \langle \vec{F} \cdot \vec{r} \rangle = \frac{1}{2} \left\langle r \frac{dU}{dr} \right\rangle = \frac{1}{2} n \langle U \rangle \text{ if } U = -\frac{k}{r^n} \quad (9.1.1.16)$$

The virial theorem for a collection of particles is:

$$\langle T \rangle = -\frac{1}{2} \left\langle \sum_{\text{particles}} \vec{F}_i \cdot \vec{r}_i + \sum_{\text{pairs}} \vec{F}_{ij} \cdot \vec{r}_{ij} \right\rangle \quad (9.1.1.17)$$

These propositions can also be written as: $2E_{\text{kin}} + E_{\text{pot}} = 0$.

Point dynamics in a moving coordinate system

Fictitious forces

The total force in a moving coordinate system can be found by subtracting the fictitious forces from the forces working in the reference frame: $\vec{F}' = \vec{F} - \vec{F}_{\text{app}}$. The different fictitious forces are:

1. Transformation of the origin: $F_{\text{or}} = -m\vec{a}_a$
2. Rotation: $\vec{F}_{\alpha} = -m\vec{\alpha} \times \vec{r}'$
3. Coriolis force: $F_{\text{cor}} = -2m\vec{\omega} \times \vec{v}$
4. Centrifugal force: $\vec{F}_{\text{cf}} = m\omega^2 \vec{r}_n' = -\vec{F}_{\text{cp}}$; $\vec{F}_{\text{cp}} = -\frac{mv^2}{r} \vec{e}_r$

Tensor notation

Transformation of the Newtonian equations of motion to $x^\alpha = x^\alpha(x)$ gives:

$$\frac{dx^\alpha}{dt} = \frac{\partial x^\alpha}{\partial \bar{x}^\beta} \frac{d\bar{x}^\beta}{dt}; \quad (9.1.1.18)$$

The chain rule gives:

$$\frac{d}{dt} \frac{dx^\alpha}{dt} = \frac{d^2 x^\alpha}{dt^2} = \frac{d}{dt} \left(\frac{\partial x^\alpha}{\partial \bar{x}^\beta} \frac{d\bar{x}^\beta}{dt} \right) = \frac{\partial x^\alpha}{\partial \bar{x}^\beta} \frac{d^2 \bar{x}^\beta}{dt^2} + \frac{d\bar{x}^\beta}{dt} \frac{d}{dt} \left(\frac{\partial x^\alpha}{\partial \bar{x}^\beta} \right) \quad (9.1.1.19)$$

so:

$$\frac{d}{dt} \frac{\partial x^\alpha}{\partial \bar{x}^\beta} = \frac{\partial}{\partial \bar{x}^\gamma} \frac{\partial x^\alpha}{\partial \bar{x}^\beta} \frac{d\bar{x}^\gamma}{dt} = \frac{\partial^2 x^\alpha}{\partial \bar{x}^\beta \partial \bar{x}^\gamma} \frac{d\bar{x}^\gamma}{dt} \quad (9.1.1.20)$$

This leads to:

$$\frac{d^2 x^\alpha}{dt^2} = \frac{\partial x^\alpha}{\partial \bar{x}^\beta} \frac{d^2 \bar{x}^\beta}{dt^2} + \frac{\partial^2 x^\alpha}{\partial \bar{x}^\beta \partial \bar{x}^\gamma} \frac{d\bar{x}^\gamma}{dt} \left(\frac{d\bar{x}^\beta}{dt} \right) \quad (9.1.1.21)$$

Hence the Newtonian equation of motion

$$m \frac{d^2 x^\alpha}{dt^2} = F^\alpha \quad (9.1.1.22)$$

will be transformed into:

$$m \left\{ \frac{d^2 x^\alpha}{dt^2} + \Gamma_{\beta\gamma}^\alpha \frac{dx^\beta}{dt} \frac{dx^\gamma}{dt} \right\} = F^\alpha \quad (9.1.1.23)$$

The apparent forces are projected from the origin to the side affected by $\Gamma_{\beta\gamma}^\alpha \frac{dx^\beta}{dt} \frac{dx^\gamma}{dt}$.

Dynamics of masspoint collections

The centre of mass

The velocity w.r.t. the centre of mass \vec{R} is given by $\vec{v} - \dot{\vec{R}}$. The coordinates of the centre of mass are given by:

$$\vec{r}_m = \frac{\sum m_i \vec{r}_i}{\sum m_i} \quad (9.1.1.24)$$

In a 2-particle system, the coordinates of the centre of mass are given by:

$$\vec{R} = \frac{m_1 \vec{r}_1 + m_2 \vec{r}_2}{m_1 + m_2} \quad (9.1.1.25)$$

With $\vec{r} = \vec{r}_1 - \vec{r}_2$, the kinetic energy becomes: $\frac{1}{2} M_{\text{tot}} \dot{\vec{R}}^2 + \frac{1}{2} \mu \dot{\vec{r}}^2$, with the *reduced mass* μ given by:

$$\frac{1}{\mu} = \frac{1}{m_1} + \frac{1}{m_2} \quad (9.1.1.26)$$

The motion of the centre of mass and relative to it can be separated:

$$\dot{\vec{L}}_{\text{outside}} = \vec{\tau}_{\text{outside}}; \quad \dot{\vec{L}}_{\text{inside}} = \vec{\tau}_{\text{inside}} \quad (9.1.1.27)$$

$$\vec{p} = m\vec{v}_m; \quad \vec{F}_{\text{ext}} = m\vec{a}_m; \quad \vec{F}_{12} = \mu\vec{u} \quad (9.1.1.28)$$

Collisions

With collisions, where B are the coordinates of the collision and C an arbitrary other position: $\vec{p} = m\vec{v}_m$ is constant, and $T = \frac{1}{2} m \vec{v}_m^2$ is constant. The changes in the *relative velocities* can be derived from: $\vec{S} = \Delta\vec{p} = \mu(\vec{v}_{\text{aft}} - \vec{v}_{\text{before}})$. Further $\Delta\vec{L}_C = \vec{CB} \times \vec{S}$, $\vec{p} \parallel \vec{S} = \text{constant}$ and \vec{L} w.r.t. B is constant.

Dynamics of rigid bodies

Moment of Inertia

The angular momentum in a moving coordinate system is given by:

$$\vec{L}' = I\vec{\omega} + \vec{L}'_n \quad (9.1.1.29)$$

where I is the *moment of inertia* with respect to a central axis, which is given by:

$$I = \sum_i m_i \vec{r}_i^2 ; \quad T' = W_{\text{rot}} = \frac{1}{2} \omega I_{ij} \vec{e}_i \vec{e}_j = \frac{1}{2} I \omega^2 \quad (9.1.1.30)$$

or, in the continuous case:

$$I = \frac{m}{V} \int r_n'^2 dV = \int r_n'^2 dm \quad (9.1.1.31)$$

Further:

$$L_i = I^{ij} \omega_j ; \quad I_{ii} = I_i ; \quad I_{ij} = I_{ji} = - \sum_k m_k x_i' x_j' \quad (9.1.1.32)$$

Steiner's theorem is: $I_{\text{w.r.t.D}} = I_{\text{w.r.t.C}} + m(DM)^2$ if axis C \parallel axis D.

Object	I	Object	I
Hollow cylinder	$I = mR^2$	Massive cylinder	$I = \frac{1}{2} mR^2$
Disc, axis in plane disc through m	$I = \frac{1}{4} mR^2$	Dumbbell	$I = \frac{1}{2} \mu R^2$
Hollow sphere	$I = \frac{2}{3} mR^2$	Massive sphere	$I = \frac{2}{5} mR^2$
Bar, axis \perp through c.o.m.	$I = \frac{1}{2} ml^2$	Bar, axis \perp through end	$I = \frac{1}{3} ml^2$
Rectangle, axis \perp plane thr. c.o.m.	$I = \frac{1}{2} m(a^2 + b^2)$	Rectangle, axis $\parallel b$ thr. m	$I = ma^2$

Principal axes

Each rigid body has (at least) 3 principal axes which stand \perp to each other. For a principal axis:

$$\frac{\partial I}{\partial \omega_x} = \frac{\partial I}{\partial \omega_y} = \frac{\partial I}{\partial \omega_z} = 0 \quad \text{so} \quad L'_n = 0 \quad (9.1.1.33)$$

The following holds: $\dot{\omega}_k = -a_{ijk} \omega_i \omega_j$ with $a_{ijk} = \frac{I_i - I_j}{I_k}$ if $I_1 \leq I_2 \leq I_3$.

Time dependence

For the torque $\vec{\tau}$:

$$\vec{\tau}' = I \ddot{\theta} ; \quad \frac{d'' \vec{L}'}{dt} = \vec{\tau}' - \vec{\omega} \times \vec{L}' \quad (9.1.1.34)$$

The torque \vec{T} is defined by: $\vec{T} = \vec{F} \times \vec{d}$.

Variational Calculus, Hamilton and Lagrange mechanics

Variational Calculus

Starting with:

$$\delta \int_a^b \mathcal{L}(q, \dot{q}, t) dt = 0 \quad \text{where} \quad \delta(a) = \delta(b) = 0 \quad \text{and} \quad \delta \left(\frac{du}{dx} \right) = \frac{d}{dx} (\delta u) \quad (9.1.1.35)$$

the equations of Lagrange can be derived:

$$\frac{d}{dt} \frac{\partial \mathcal{L}}{\partial \dot{q}_i} = \frac{\partial \mathcal{L}}{\partial q_i} \quad (9.1.1.36)$$

When there are additional conditions applying to the variational problem $\delta J(u) = 0$ of the type $K(u) = \text{constant}$, the new problem becomes: $\delta J(u) - \lambda \delta K(u) = 0$.

Hamilton mechanics

The *Lagrangian* is given by: $\mathcal{L} = \sum T(\dot{q}_i) - V(q_i)$. The *Hamiltonian* is given by: $H = \sum \dot{q}_i p_i - \mathcal{L}$. In two dimensions: $\mathcal{L} = T - U = \frac{1}{2}m(\dot{r}^2 + r^2\dot{\phi}^2) - U(r, \phi)$.

If the coordinates used are *canonical* the *Hamilton equations* are the equations of motion for the system:

$$\frac{dq_i}{dt} = \frac{\partial H}{\partial p_i}; \quad \frac{dp_i}{dt} = -\frac{\partial H}{\partial q_i} \quad (9.1.1.37)$$

Coordinates are canonical if the following holds: $\{q_i, q_j\} = 0$, $\{p_i, p_j\} = 0$, $\{q_i, p_j\} = \delta_{ij}$ where $\{, \}$ is the *Poisson bracket*:

$$\{A, B\} = \sum_i \left[\frac{\partial A}{\partial q_i} \frac{\partial B}{\partial p_i} - \frac{\partial A}{\partial p_i} \frac{\partial B}{\partial q_i} \right] \quad (9.1.1.38)$$

The *Hamiltonian* of an harmonic oscillator is given by $H(x, p) = p^2/2m + \frac{1}{2}m\omega^2 x^2$. With new coordinates (θ, I) , obtained by the canonical transform $x = \sqrt{2I/m\omega} \cos(\theta)$ and $p = -\sqrt{2Im\omega} \sin(\theta)$, with inverse $\theta = \arctan(-p/m\omega x)$ and $I = p^2/2m\omega + \frac{1}{2}m\omega x^2$ it follows: $H(\theta, I) = \omega I$.

The *Hamiltonian* of a charged particle with charge q in an external electromagnetic field is given by:

$$H = \frac{1}{2m} (\vec{p} - q\vec{A})^2 + qV \quad (9.1.1.39)$$

This *Hamiltonian* can be derived from the *Hamiltonian* of a free particle $H = p^2/2m$ with the transform $\vec{p} \rightarrow \vec{p} - q\vec{A}$ and $H \rightarrow H - qV$. This is elegant from a relativistic point of view: it is equivalent to the transformation of the momentum 4-vector $p^\alpha \rightarrow p^\alpha - qA^\alpha$. A gauge transform on the potentials A^α corresponds with a canonical transform, which make the *Hamilton equations* the equations of motion for the system.

Motion near equilibrium, linearization

For natural systems near equilibrium the following equations are valid:

$$\left(\frac{\partial V}{\partial q_i} \right)_0 = 0; \quad V(q) = V(0) + V_{ik} q_i q_k \text{ with } V_{ik} = \left(\frac{\partial^2 V}{\partial q_i \partial q_k} \right)_0 \quad (9.1.1.40)$$

With $T = \frac{1}{2}(M_{ik}\dot{q}_i\dot{q}_k)$ one obtains the set of equations $M\ddot{q} + Vq = 0$. If $q_i(t) = a_i \exp(i\omega t)$ is substituted, this set of equations has solutions if $\det(V - \omega^2 M) = 0$. This leads to the eigenfrequencies of the problem: $\omega_k^2 = \frac{a_k^T V a_k}{a_k^T M a_k}$. If the equilibrium is stable: $\forall k$ that $\omega_k^2 > 0$. The general solution is a superposition of eigenvibrations.

Phase space, Liouville's equation

In phase space:

$$\nabla = \left(\sum_i \frac{\partial}{\partial q_i}, \sum_i \frac{\partial}{\partial p_i} \right) \text{ so } \nabla \cdot \vec{v} = \sum_i \left(\frac{\partial}{\partial q_i} \frac{\partial H}{\partial p_i} - \frac{\partial}{\partial p_i} \frac{\partial H}{\partial q_i} \right) \quad (9.1.1.41)$$

If the equation of continuity, $\partial_t \rho + \nabla \cdot (\rho \vec{v}) = 0$ holds, this can be written as:

$$\{\rho, H\} + \frac{\partial \rho}{\partial t} = 0 \quad (9.1.1.42)$$

For an arbitrary quantity A :

$$\frac{dA}{dt} = \{A, H\} + \frac{\partial A}{\partial t} \quad (9.1.1.43)$$

Liouville's theorem can then be written as:

$$\frac{d\rho}{dt} = 0; \quad \text{or } \int \rho dq = \text{constant} \quad (9.1.1.44)$$

Generating functions

Starting with the coordinate transformation:

$$\begin{cases} Q_i = Q_i(q_i, p_i, t) \\ P_i = P_i(q_i, p_i, t) \end{cases} \quad (9.1.1.45)$$

one can derive the following *Hamilton equations* with the new *Hamiltonian* K :

$$\frac{dQ_i}{dt} = \frac{\partial K}{\partial P_i}; \quad \frac{dP_i}{dt} = -\frac{\partial K}{\partial Q_i} \quad (9.1.1.46)$$

Now, a distinction between 4 cases can be made:

1. If $p_i \dot{q}_i - H = P_i \dot{Q}_i - K(P_i, Q_i, t) - \frac{dF_1(q_i, Q_i, t)}{dt}$, the coordinates follow from:

$$p_i = \frac{\partial F_1}{\partial q_i}; \quad P_i = -\frac{\partial F_1}{\partial Q_i}; \quad K = H + \frac{\partial F_1}{\partial t} \quad (9.1.1.47)$$

2. If $p_i \dot{q}_i - H = -\dot{P}_i Q_i - K(P_i, Q_i, t) + \frac{dF_2(q_i, P_i, t)}{dt}$, the coordinates follow from:

$$p_i = \frac{\partial F_2}{\partial q_i}; \quad Q_i = \frac{\partial F_2}{\partial P_i}; \quad K = H + \frac{\partial F_2}{\partial t} \quad (9.1.1.48)$$

3. If $-\dot{p}_i q_i - H = P_i \dot{Q}_i - K(P_i, Q_i, t) + \frac{dF_3(p_i, Q_i, t)}{dt}$, the coordinates follow from:

$$q_i = -\frac{\partial F_3}{\partial p_i}; \quad P_i = -\frac{\partial F_3}{\partial Q_i}; \quad K = H + \frac{\partial F_3}{\partial t} \quad (9.1.1.49)$$

4. If $-\dot{p}_i q_i - H = -\dot{P}_i Q_i - K(P_i, Q_i, t) + \frac{dF_4(p_i, P_i, t)}{dt}$, the coordinates follow from:

$$q_i = -\frac{\partial F_4}{\partial p_i}; \quad Q_i = \frac{\partial F_4}{\partial P_i}; \quad K = H + \frac{\partial F_4}{\partial t} \quad (9.1.1.50)$$

The functions F_1 , F_2 , F_3 and F_4 are called *generating functions*.

This page titled [9.1.1: Mechanics](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

9.1.2: Oscillations

Harmonic oscillation

The general form of a harmonic oscillation is: $\Psi(t) = \hat{\Psi}e^{i(\omega t \pm \varphi)} \equiv \hat{\Psi} \cos(\omega t \pm \varphi)$,

where $\hat{\Psi}$ is the *amplitude*. A superposition of several harmonic oscillations *with the same frequency* results in another harmonic oscillation:

$$\sum_i \hat{\Psi}_i \cos(\alpha_i \pm \omega t) = \hat{\Phi} \cos(\beta \pm \omega t) \quad (9.1.2.1)$$

with:

$$\tan(\beta) = \frac{\sum_i \hat{\Psi}_i \sin(\alpha_i)}{\sum_i \hat{\Psi}_i \cos(\alpha_i)} \quad \text{and} \quad \hat{\Phi}^2 = \sum_i \hat{\Psi}_i^2 + 2 \sum_{j>i} \sum_i \hat{\Psi}_i \hat{\Psi}_j \cos(\alpha_i - \alpha_j) \quad (9.1.2.2)$$

For harmonic oscillations: $\int x(t)dt = \frac{x(t)}{i\omega}$ and $\frac{d^n x(t)}{dt^n} = (i\omega)^n x(t)$.

Mechanic oscillation

For a spring with constant C and damping k which is connected to a mass M , to which a periodic force $F(t) = \hat{F} \cos(\omega t)$ is applied the equation of motion is $m\ddot{x} = F(t) - k\dot{x} - Cx$. With complex amplitudes, this becomes $-m\omega^2 x = F - Cx - ik\omega x$. With $\omega_0^2 = C/m$ it follows that:

$$x = \frac{F}{m(\omega_0^2 - \omega^2) + ik\omega} \quad , \text{ and for the velocity: } \dot{x} = \frac{F}{i\sqrt{Cm}\delta + k} \quad (9.1.2.3)$$

where $\delta = \frac{\omega}{\omega_0} - \frac{\omega_0}{\omega}$. The quantity $Z = F/\dot{x}$ is called the *impedance* of the system. The *quality* of the system is given by $Q = \frac{\sqrt{Cm}}{k}$.

The frequency with minimal $|Z|$ is called the *velocity resonance frequency*. This is equal to ω_0 . In the *resonance curve* $|Z|/\sqrt{Cm}$ is plotted against ω/ω_0 . The width of this curve is characterized by the points where $|Z(\omega)| = |Z(\omega_0)|\sqrt{2}$. At these points: $R = X$ and $\delta = \pm Q^{-1}$, and the width is $2\Delta\omega_B = \omega_0/Q$.

The *stiffness* of an oscillating system is given by F/x . The *amplitude resonance frequency* ω_A is the frequency where $i\omega Z$ is a minimum. This is the case for $\omega_A = \omega_0 \sqrt{1 - \frac{1}{2}Q^2}$.

The *damping frequency* ω_D is a measure for the time in which an oscillating system comes to rest. It is given by $\omega_D = \omega_0 \sqrt{1 - \frac{1}{4Q^2}}$. A weak damped oscillation ($k^2 < 4mC$) dies out after $T_D = 2\pi/\omega_D$. For a *critically damped* oscillation ($k^2 = 4mC$) $\omega_D = 0$. A strong damped oscillation ($k^2 > 4mC$) decays like (if $k^2 \gg 4mC$) $x(t) \approx x_0 \exp(-t/\tau)$.

Electric oscillations

The *impedance* is given by: $Z = R + iX$. The phase angle is $\varphi := \arctan(X/R)$. The impedance of a resistor is R , of a capacitor $1/i\omega C$ and of a self inductor $i\omega L$. The quality of a coil is $Q = \omega L/R$. The total impedance in case several elements are connected is given by:

1. Series connection: $V = IZ$,

$$Z_{\text{tot}} = \sum_i Z_i, \quad L_{\text{tot}} = \sum_i L_i, \quad \frac{1}{C_{\text{tot}}} = \sum_i \frac{1}{C_i}, \quad Q = \frac{Z_0}{R}, \quad Z = R(1 + iQ\delta) \quad (9.1.2.4)$$

2. Parallel connection: $V = IZ$,

$$\frac{1}{Z_{\text{tot}}} = \sum_i \frac{1}{Z_i}, \quad \frac{1}{L_{\text{tot}}} = \sum_i \frac{1}{L_i}, \quad C_{\text{tot}} = \sum_i C_i, \quad Q = \frac{R}{Z_0}, \quad Z = \frac{R}{1 + iQ\delta} \quad (9.1.2.5)$$

Here, $Z_0 = \sqrt{\frac{L}{C}}$ and $\omega_0 = \frac{1}{\sqrt{LC}}$.

The power from a source is given by $P(t) = V(t) \cdot I(t)$, so $\langle P \rangle_t = \hat{V}_{\text{eff}} \hat{I}_{\text{eff}} \cos(\Delta\phi)$
 $= \frac{1}{2} \hat{V} \hat{I} \cos(\phi_v - \phi_i) = \frac{1}{2} \hat{I}^2 \text{Re}(Z) = \frac{1}{2} \hat{V}^2 \text{Re}(1/Z)$, where $\cos(\Delta\phi)$ is the work factor.

Waves in long conductors

If cables are used for signal transfer, e.g. coax cables then: $Z_0 = \sqrt{\frac{dL}{dx} \frac{dx}{dC}}$.

The transmission velocity is given by $v = \sqrt{\frac{dx}{dL} \frac{dx}{dC}}$.

Coupled conductors and transformers

For two coils enclosing each others flux if Φ_{12} is the part of the flux originating from I_2 through coil 2 which is enclosed by coil 1, then $\Phi_{12} = M_{12}I_2$, $\Phi_{21} = M_{21}I_1$. The coefficients of mutual induction M_{ij} is given by:

$$M_{12} = M_{21} := M = k\sqrt{L_1 L_2} = \frac{N_1 \Phi_1}{I_2} = \frac{N_2 \Phi_2}{I_1} \sim N_1 N_2 \quad (9.1.2.6)$$

where $0 \leq k \leq 1$ is the *coupling factor*. For a transformer $k \approx 1$. At full load:

$$\frac{V_1}{V_2} = \frac{I_2}{I_1} = -\frac{i\omega M}{i\omega L_2 + R_{\text{load}}} \approx -\sqrt{\frac{L_1}{L_2}} = -\frac{N_1}{N_2} \quad (9.1.2.7)$$

Pendulums

The oscillation time $T = 1/f$, for different types of pendulums is given by:

- Oscillating spring: $T = 2\pi\sqrt{m/C}$ if the spring force is given by $F = C \cdot \Delta l$.
- Physical pendulum: $T = 2\pi\sqrt{I/\tau}$ with τ the moment of force and I the moment of inertia.
- Torsion pendulum: $T = 2\pi\sqrt{I/\kappa}$ where $\kappa = \frac{2lm}{\pi r^4 \Delta\varphi}$ is the constant of torsion and I the moment of inertia.
- Mathematical pendulum: $T = 2\pi\sqrt{l/g}$ with g the acceleration of gravity and l the length of the pendulum.

This page titled [9.1.2: Oscillations](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

9.1.3: Waves

The wave equation

The general form of the wave equation is: $\square u = 0$, or:

$$\nabla^2 u - \frac{1}{v^2} \frac{\partial^2 u}{\partial t^2} = \frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} + \frac{\partial^2 u}{\partial z^2} - \frac{1}{v^2} \frac{\partial^2 u}{\partial t^2} = 0 \quad (9.1.3.1)$$

where u is the disturbance and v the *propagation velocity*. In general $v = f\lambda$ holds. By definition $k\lambda = 2\pi$ and $\omega = 2\pi f$.

In principle, there are two types of waves:

1. Longitudinal waves: for these $\vec{k} \parallel \vec{v} \parallel \vec{u}$ holds.
2. Transversal waves: for these $\vec{k} \parallel \vec{v} \perp \vec{u}$ holds.

The *phase velocity* is given by $v_{\text{ph}} = \omega/k$. The *group velocity* is given by:

$$v_g = \frac{d\omega}{dk} = v_{\text{ph}} + k \frac{dv_{\text{ph}}}{dk} = v_{\text{ph}} \left(1 - \frac{k}{n} \frac{dn}{dk} \right) \quad (9.1.3.2)$$

where n is the refractive index of the medium. If v_{ph} does not depend on ω then: $v_{\text{ph}} = v_g$. In a dispersive medium it is possible that $v_g > v_{\text{ph}}$ or $v_g < v_{\text{ph}}$, and $v_g \cdot v_f = c^2$. If one wants to transfer information with a wave, e.g. by modulation of an EM wave, the information travels with the velocity at which a change in the electromagnetic field propagates. This velocity is often almost equal to the group velocity.

For some media, the propagation velocity follows from:

- Pressure waves in a liquid or gas: $v = \sqrt{\kappa/\rho}$, where κ is the modulus of compression.
- Further for pressure waves in a gas: $v = \sqrt{\gamma p/\rho} = \sqrt{\gamma RT/M}$.
- Pressure waves in a thin solid bar with diameter $\ll \lambda$: $v = \sqrt{E/\rho}$
- Waves in a string: $v = \sqrt{F_{\text{span}} l/m}$
- Surface waves on a liquid: $v = \sqrt{\left(\frac{g\lambda}{2\pi} + \frac{2\pi\gamma}{\rho\lambda} \right) \tanh\left(\frac{2\pi h}{\lambda} \right)}$

where h is the depth of the liquid and γ the surface tension. If $h \ll \lambda$ then $v \approx \sqrt{gh}$ holds.

Solutions of the wave equation

Plane waves

In n dimensions a harmonic plane wave is defined by:

$$u(\vec{x}, t) = 2^n \hat{u} \cos(\omega t) \sum_{i=1}^n \sin(k_i x_i) \quad (9.1.3.3)$$

The equation for a harmonic traveling plane wave is: $u(\vec{x}, t) = \hat{u} \cos(\vec{k} \cdot \vec{x} \pm \omega t + \varphi)$

If waves reflect at the end of a spring this will result in a change in phase. A fixed end imposes a phase change of $\pi/2$ to the reflected wave, with boundary condition $u(l) = 0$. A loose end yields no change in the phase of the reflected wave, with boundary condition $(\partial u / \partial x)_l = 0$.

If an observer is moving w.r.t. the wave with a velocity v_{obs} , they will observe a change in frequency: the *Doppler effect*. This is given by: $\frac{f}{f_0} = \frac{v_f - v_{\text{obs}}}{v_f}$.

Spherical waves

When the situation is spherically symmetric, the homogeneous wave equation is given by:

$$\frac{1}{v^2} \frac{\partial^2 (ru)}{\partial t^2} - \frac{\partial^2 (ru)}{\partial r^2} = 0 \quad (9.1.3.4)$$

with a general solution:

$$u(r, t) = C_1 \frac{f(r - vt)}{r} + C_2 \frac{g(r + vt)}{r} \quad (9.1.3.5)$$

Cylindrical waves

When the situation has a cylindrical symmetry, the homogeneous wave equation becomes:

$$\frac{1}{v^2} \frac{\partial^2 u}{\partial t^2} - \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial u}{\partial r} \right) = 0 \quad (9.1.3.6)$$

This is a Bessel equation, with solutions that can be written as Hankel functions. For sufficient large values of r these are approximated by:

$$u(r, t) = \frac{\hat{u}}{\sqrt{r}} \cos(k(r \pm vt)) \quad (9.1.3.7)$$

The general solution in one dimension

Starting from the equation:

$$\frac{\partial^2 u(x, t)}{\partial t^2} = \sum_{m=0}^N \left(b_m \frac{\partial^m}{\partial x^m} \right) u(x, t) \quad (9.1.3.8)$$

where $b_m \in \mathbb{R}$. Substituting $u(x, t) = Ae^{i(kx - \omega t)}$ gives two solutions $\omega_j = \omega_j(k)$ as dispersion relations. The general solution is given by:

$$u(x, t) = \int_{-\infty}^{\infty} \left(a(k) e^{i(kx - \omega_1(k)t)} + b(k) e^{i(kx - \omega_2(k)t)} \right) dk \quad (9.1.3.9)$$

Because in general the frequencies ω_j are non-linear in k there is dispersion and the solution cannot be written any more as a sum of functions depending only on $x \pm vt$: the wave front transforms.

The stationary phase method

Usually the *Fourier integrals* of the previous section cannot be calculated exactly. If $\omega_j(k) \in \mathbb{R}$ the stationary phase method can be applied. Assuming that $a(k)$ is only a slowly varying function of k , one can state that the parts of the k -axis where the phase of $kx - \omega(k)t$ changes rapidly will give no net contribution to the integral because the exponent oscillates rapidly there. The only areas contributing significantly to the integral are areas with a stationary phase, determined by $\frac{d}{dk}(kx - \omega(k)t) = 0$. Now the following approximation is possible:

$$\int_{-\infty}^{\infty} a(k) e^{i(kx - \omega(k)t)} dk \approx \sum_{i=1}^N \sqrt{\frac{2\pi}{\frac{d^2 \omega(k_i)}{dk_i^2}}} \exp \left[-i \frac{1}{4} \pi + i(k_i x - \omega(k_i)t) \right] \quad (9.1.3.10)$$

Green functions for the initial-value problem

This method is preferable if the solutions deviate strongly from the stationary solutions, like point-like excitations. Starting with the wave equation in one dimension, with $\nabla^2 = \partial^2 / \partial x^2$ if $Q(x, x', t)$ is the solution with initial values $Q(x, x', 0) = \delta(x - x')$ and $\frac{\partial Q(x, x', 0)}{\partial t} = 0$, and $P(x, x', t)$ the solution with initial values $P(x, x', 0) = 0$ and $\frac{\partial P(x, x', 0)}{\partial t} = \delta(x - x')$, then the solution of the wave equation with arbitrary initial conditions $f(x) = u(x, 0)$ and $g(x) = \frac{\partial u(x, 0)}{\partial t}$ is given by:

$$u(x, t) = \int_{-\infty}^{\infty} f(x') Q(x, x', t) dx' + \int_{-\infty}^{\infty} g(x') P(x, x', t) dx' \quad (9.1.3.11)$$

P and Q are called the *propagators*. They are defined by:

$$Q(x, x', t) = \frac{1}{2} [\delta(x - x' - vt) + \delta(x - x' + vt)]$$

$$P(x, x', t) = \begin{cases} \frac{1}{2v} & \text{if } |x - x'| < vt \\ 0 & \text{if } |x - x'| > vt \end{cases}$$

Further the relation: $Q(x, x', t) = \frac{\partial P(x, x', t)}{\partial t}$ holds.

Waveguides and resonating cavities

The boundary conditions for a perfect conductor can be derived from *Maxwell's equations*. If \vec{n} is a unit vector \perp the surface, pointing from 1 to 2, and \vec{K} is a surface current density, then:

$$\begin{aligned} \vec{n} \cdot (\vec{D}_2 - \vec{D}_1) &= \sigma & \vec{n} \times (\vec{E}_2 - \vec{E}_1) &= 0 \\ \vec{n} \cdot (\vec{B}_2 - \vec{B}_1) &= 0 & \vec{n} \times (\vec{H}_2 - \vec{H}_1) &= \vec{K} \end{aligned} \quad (9.1.3.12)$$

In a waveguide because of the cylindrical symmetry: $\vec{E}(\vec{x}, t) = \vec{\mathcal{E}}(x, y)e^{i(kz - \omega t)}$ and $\vec{B}(\vec{x}, t) = \vec{\mathcal{B}}(x, y)e^{i(kz - \omega t)}$ holds. From this one can now deduce that, if \mathcal{B}_z and \mathcal{E}_z are not $\equiv 0$:

$$\begin{aligned} \mathcal{B}_x &= \frac{i}{\varepsilon\mu\omega^2 - k^2} \left(k \frac{\partial \mathcal{B}_z}{\partial x} - \varepsilon\mu\omega \frac{\partial \mathcal{E}_z}{\partial y} \right) & \mathcal{B}_y &= \frac{i}{\varepsilon\mu\omega^2 - k^2} \left(k \frac{\partial \mathcal{B}_z}{\partial y} + \varepsilon\mu\omega \frac{\partial \mathcal{E}_z}{\partial x} \right) \\ \mathcal{E}_x &= \frac{i}{\varepsilon\mu\omega^2 - k^2} \left(k \frac{\partial \mathcal{E}_z}{\partial x} + \varepsilon\mu\omega \frac{\partial \mathcal{B}_z}{\partial y} \right) & \mathcal{E}_y &= \frac{i}{\varepsilon\mu\omega^2 - k^2} \left(k \frac{\partial \mathcal{E}_z}{\partial y} - \varepsilon\mu\omega \frac{\partial \mathcal{B}_z}{\partial x} \right) \end{aligned} \quad (9.1.3.13)$$

Now one can distinguish between three cases:

1. $\mathcal{B}_z \equiv 0$: the Transverse Magnetic Modes (TM). Boundary condition: $\mathcal{E}_z|_{\text{surf}} = 0$.
2. $\mathcal{E}_z \equiv 0$: the Transverse Electric Modes (TE). Boundary condition: $\frac{\partial \mathcal{B}_z}{\partial n}|_{\text{surf}} = 0$.

For the TE and TM modes this results in an eigenvalue problem for \mathcal{E}_z resp. \mathcal{B}_z with boundary conditions:

$$\left(\frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} \right) \psi = -\gamma^2 \psi \text{ with eigenvalues } \gamma^2 := \varepsilon\mu\omega^2 - k^2 \quad (9.1.3.14)$$

This has a discrete solution ψ_ℓ with eigenvalue γ_ℓ^2 : $k = \sqrt{\varepsilon\mu\omega^2 - \gamma_\ell^2}$. For $\omega < \omega_\ell$, k is imaginary and the wave is damped. Therefore, ω_ℓ is called the *cut-off frequency*. In rectangular conductors the following expression can be found for the cut-off frequency for modes $\text{TE}_{m,n}$ or $\text{TM}_{m,n}$:

$$\lambda_\ell = \frac{2}{\sqrt{(m/a)^2 + (n/b)^2}} \quad (9.1.3.15)$$

3. \mathcal{E}_z and \mathcal{B}_z are zero everywhere for the Transversal Electro-Magnetic Modes (TEM). Then: $k = \pm\omega\sqrt{\varepsilon\mu}$ and $v_f = v_g$, just as if there were no waveguide. Further $k \in \mathbb{R}$, so no cut-off frequency exists.

In a rectangular, three dimensional resonating cavity with edges a , b and c the possible wave numbers are given by: $k_x = \frac{n_1\pi}{a}$, $k_y = \frac{n_2\pi}{b}$, $k_z = \frac{n_3\pi}{c}$ This results in the possible frequencies $f = vk/2\pi$ in the cavity:

$$f = \frac{v}{2} \sqrt{\frac{n_x^2}{a^2} + \frac{n_y^2}{b^2} + \frac{n_z^2}{c^2}} \quad (9.1.3.16)$$

For a cubic cavity, with $a = b = c$, the possible number of oscillating modes N_L for longitudinal waves is given by:

$$N_L = \frac{4\pi a^3 f^3}{3v^3} \quad (9.1.3.17)$$

Because transverse waves have two possible polarizations $N_T = 2N_L$ holds for them.

Non-linear wave equations

The *Van der Pol* equation is given by:

$$\frac{d^2x}{dt^2} - \varepsilon\omega_0(1 - \beta x^2)\frac{dx}{dt} + \omega_0^2x = 0 \quad (9.1.3.18)$$

βx^2 can be ignored for very small values of the amplitude. Substitution of $x \sim e^{i\omega t}$ gives: $\omega = \frac{1}{2}\omega_0(i\varepsilon \pm 2\sqrt{1 - \frac{1}{2}\varepsilon^2})$. The lowest-order instabilities grow as $\frac{1}{2}\varepsilon\omega_0$. While x is growing, the 2nd term becomes larger and which limits the growth. Oscillations on a time scale $\sim \omega_0^{-1}$ can exist. If x is expanded as $x = x^{(0)} + \varepsilon x^{(1)} + \varepsilon^2 x^{(2)} + \dots$ and this is substituted one obtains, additional periodic, *secular terms* $\sim \varepsilon t$. If it is assumed that there exist timescales τ_n , $0 \leq \tau \leq N$ with $\partial\tau_n/\partial t = \varepsilon^n$ and if the secular terms are put to 0 one obtains:

$$\frac{d}{dt} \left\{ \frac{1}{2} \left(\frac{dx}{dt} \right)^2 + \frac{1}{2} \omega_0^2 x^2 \right\} = \varepsilon\omega_0(1 - \beta x^2) \left(\frac{dx}{dt} \right)^2 \quad (9.1.3.19)$$

This is an energy equation. Energy is conserved if the left-hand side is 0. If $x^2 > 1/\beta$, the right-hand side changes sign and an increase in energy changes into a decrease of energy. This mechanism limits the growth of oscillations.

The *Korteweg-De Vries* equation is given by:

$$\frac{\partial u}{\partial t} + \frac{\partial u}{\partial x} - \underbrace{au \frac{\partial u}{\partial x}}_{\text{non-lin}} + \underbrace{b^2 \frac{\partial^3 u}{\partial x^3}}_{\text{dispersive}} = 0 \quad (9.1.3.20)$$

This equation is for example a model for ion-acoustic waves in a plasma. For this equation, soliton solutions of the following form exist:

$$u(x - ct) = \frac{-d}{\cosh^2(e(x - ct))} \quad (9.1.3.21)$$

with $c = 1 + \frac{1}{3}ad$ and $e^2 = ad/(12b^2)$.

This page titled [9.1.3: Waves](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

CHAPTER OVERVIEW

9.1.4: Physical Constants, Units, Del Operator

[9.1.4.1: Physical Constants](#)

[9.1.4.2: Prefixes for Powers of 10](#)

[9.1.4.3: SI Units](#)

[9.1.4.4: The Del-operator](#)

This page titled [9.1.4: Physical Constants, Units, Del Operator](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

9.1.4.1: Physical Constants

Name	Symbol	Value	Unit
Number π	π	3.14159265358979323846	
Number e	e	2.71828182845904523536	
Euler's constant		0.577215664901532860606	
Elementary charge	e	$1.60217733 \cdot 10^{-19}$	C
Gravitational constant	G, κ	$6.67259 \cdot 10^{-11}$	$\text{m}^3 \text{kg}^{-1} \text{s}^{-2}$
Fine-structure constant	$\alpha = e^2/2hc\varepsilon_0$	$\approx 1/137$	
Speed of light in vacuum	c	$2.99792458 \cdot 10^8$	m/s (def)
Permittivity of the vacuum	ε_0	$8.854187 \cdot 10^{-12}$	F/m
Permeability of the vacuum	μ_0	$4\pi \cdot 10^{-7}$	H/m
$(4\pi\varepsilon_0)^{-1}$		$8.9876 \cdot 10^9$	$\text{Nm}^2 \text{C}^{-2}$
Planck's constant	h	$6.6260755 \cdot 10^{-34}$	Js
Dirac's constant	$\hbar = h/2\pi$	$1.0545727 \cdot 10^{-34}$	Js
Bohr magneton	$\mu_B = e\hbar/2m_e$	$9.2741 \cdot 10^{-24}$	Am^2
Bohr radius	a_0	0.52918	Å
Rydberg's constant	Ry	13.595	eV
Electron Compton wavelength	$\lambda_{Ce} = h/m_e c$	$2.2463 \cdot 10^{-12}$	m
Proton Compton wavelength	$\lambda_{Cp} = h/m_p c$	$1.3214 \cdot 10^{-15}$	m
Reduced mass of the H-atom	μ_H	$9.1045755 \cdot 10^{-31}$	kg
Stefan-Boltzmann's constant	σ	$5.67032 \cdot 10^{-8}$	$\text{Wm}^{-2} \text{K}^{-4}$
Wien's constant	k_W	$2.8978 \cdot 10^{-3}$	mK
Molar gasconstant	R	8.31441	$\text{J}\cdot\text{mol}^{-1}\cdot\text{K}^{-1}$
Avogadro's constant	N_A	$6.0221367 \cdot 10^{23}$	mol^{-1}
Boltzmann's constant	$k = R/N_A$	$1.380658 \cdot 10^{-23}$	J/K
Electron mass	m_e	$9.1093897 \cdot 10^{-31}$	kg
Proton mass	m_p	$1.6726231 \cdot 10^{-27}$	kg
Neutron mass	m_n	$1.674954 \cdot 10^{-27}$	kg
Elementary mass unit	$m_u = \frac{1}{12}m(^{12}_6\text{C})$	$1.6605656 \cdot 10^{-27}$	kg
Nuclear magneton	μ_N	$5.0508 \cdot 10^{-27}$	J/T
Diameter of the Sun	D_\odot	$1392 \cdot 10^6$	m

Name	Symbol	Value	Unit
Mass of the Sun	M_{\odot}	$1.989 \cdot 10^{30}$	kg
Rotational period of the Sun	T_{\odot}	25.38	days
Radius of Earth	R_A	$6.378 \cdot 10^6$	m
Mass of Earth	M_A	$5.976 \cdot 10^{24}$	kg
Rotational period of Earth	T_A	23.96	hours
Earth orbital period	Tropical year	365.24219879	days
Astronomical unit	AU	$1.4959787066 \cdot 10^{11}$	m
Light year	lj	$9.4605 \cdot 10^{15}$	m
Parsec	pc	$3.0857 \cdot 10^{16}$	m
Hubble constant	H	$\approx (75 \pm 25)$	$\text{km} \cdot \text{s}^{-1} \cdot \text{Mpc}^{-1}$

This page titled [9.1.4.1: Physical Constants](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

9.1.4.2: Prefixes for Powers of 10

yotta	Y	10^{24}	giga	G	10^9	deci	d	10^{-1}	pico	p	10^{-12}
zetta	Z	10^{21}	mega	M	10^6	centi	c	10^{-2}	femto	f	10^{-15}
exa	E	10^{18}	kilo	k	10^3	milli	m	10^{-3}	atto	a	10^{-18}
peta	P	10^{15}	hecto	h	10^2	micro	μ	10^{-6}	zepto	z	10^{-21}
tera	T	10^{12}	deca	da	10	nano	n	10^{-9}	yocto	y	10^{-24}

This page titled [9.1.4.2: Prefixes for Powers of 10](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

9.1.4.3: SI Units

SI Base Units

Quantity	Unit	Sym.
Length	metre	m
Mass	kilogram	kg
Time	second	s
Therm. temp.	kelvin	K
Electr. current	ampere	A
Luminous intens.	candela	cd
Amount of subst.	mol	mol
Plane angle	radian	rad
solid angle	sterradian	sr

SI Derivative Units

Quantity	Unit	Sym.	Derivation
Frequency	hertz	Hz	s^{-1}
Force	newton	N	$kg \cdot m \cdot s^{-2}$
Pressure	pascal	Pa	$N \cdot m^{-2}$
Energy	joule	J	$N \cdot m$
Power	watt	W	$J \cdot s^{-1}$
Charge	coulomb	C	$A \cdot s$
El. Potential	volt	V	$W \cdot A^{-1}$
El. Capacitance	farad	F	$C \cdot V^{-1}$
El. Resistance	ohm	Ω	$V \cdot A^{-1}$
El. Conductance	siemens	S	$A \cdot V^{-1}$
Mag. flux	weber	Wb	$V \cdot s$
Mag. flux density	tesla	T	$Wb \cdot m^{-2}$

Inductance	henry	H	$\text{Wb} \cdot \text{A}^{-1}$
Luminous flux	lumen	lm	$\text{cd} \cdot \text{sr}$
Illuminance	lux	lx	$\text{lm} \cdot \text{m}^{-2}$
Activity	becquerel	Bq	s^{-1}
Absorbed dose	gray	Gy	$\text{J} \cdot \text{kg}^{-1}$
Dose equivalent	sievert	Sv	$\text{J} \cdot \text{kg}^{-1}$

This page titled [9.1.4.3: SI Units](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

9.1.4.4: The Del-operator

The ∇ -operator

In cartesian coordinates (x, y, z) :

$$\vec{\nabla} = \frac{\partial}{\partial x} \vec{e}_x + \frac{\partial}{\partial y} \vec{e}_y + \frac{\partial}{\partial z} \vec{e}_z, \quad \text{grad} f = \vec{\nabla} f = \frac{\partial f}{\partial x} \vec{e}_x + \frac{\partial f}{\partial y} \vec{e}_y + \frac{\partial f}{\partial z} \vec{e}_z \quad (9.1.4.4.1)$$

$$\text{div } \vec{a} = \vec{\nabla} \cdot \vec{a} = \frac{\partial a_x}{\partial x} + \frac{\partial a_y}{\partial y} + \frac{\partial a_z}{\partial z}, \quad \nabla^2 f = \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2} + \frac{\partial^2 f}{\partial z^2} \quad (9.1.4.4.2)$$

$$\text{rot } \vec{a} = \vec{\nabla} \times \vec{a} = \left(\frac{\partial a_z}{\partial y} - \frac{\partial a_y}{\partial z} \right) \vec{e}_x + \left(\frac{\partial a_x}{\partial z} - \frac{\partial a_z}{\partial x} \right) \vec{e}_y + \left(\frac{\partial a_y}{\partial x} - \frac{\partial a_x}{\partial y} \right) \vec{e}_z \quad (9.1.4.4.3)$$

In cylinder coordinates (r, φ, z) holds:

$$\vec{\nabla} = \frac{\partial}{\partial r} \vec{e}_r + \frac{1}{r} \frac{\partial}{\partial \varphi} \vec{e}_\varphi + \frac{\partial}{\partial z} \vec{e}_z, \quad \text{grad} f = \frac{\partial f}{\partial r} \vec{e}_r + \frac{1}{r} \frac{\partial f}{\partial \varphi} \vec{e}_\varphi + \frac{\partial f}{\partial z} \vec{e}_z \quad (9.1.4.4.4)$$

$$\text{div } \vec{a} = \frac{\partial a_r}{\partial r} + \frac{a_r}{r} + \frac{1}{r} \frac{\partial a_\varphi}{\partial \varphi} + \frac{\partial a_z}{\partial z}, \quad \nabla^2 f = \frac{\partial^2 f}{\partial r^2} + \frac{1}{r} \frac{\partial f}{\partial r} + \frac{1}{r^2} \frac{\partial^2 f}{\partial \varphi^2} + \frac{\partial^2 f}{\partial z^2} \quad (9.1.4.4.5)$$

$$\text{rot } \vec{a} = \left(\frac{1}{r} \frac{\partial a_z}{\partial \varphi} - \frac{\partial a_\varphi}{\partial z} \right) \vec{e}_r + \left(\frac{\partial a_r}{\partial z} - \frac{\partial a_z}{\partial r} \right) \vec{e}_\varphi + \left(\frac{\partial a_\varphi}{\partial r} + \frac{a_\varphi}{r} - \frac{1}{r} \frac{\partial a_r}{\partial \varphi} \right) \vec{e}_z \quad (9.1.4.4.6)$$

In spherical coordinates (r, θ, φ) :

$$\begin{aligned} \vec{\nabla} &= \frac{\partial}{\partial r} \vec{e}_r + \frac{1}{r} \frac{\partial}{\partial \theta} \vec{e}_\theta + \frac{1}{r \sin \theta} \frac{\partial}{\partial \varphi} \vec{e}_\varphi \\ \text{grad} f &= \frac{\partial f}{\partial r} \vec{e}_r + \frac{1}{r} \frac{\partial f}{\partial \theta} \vec{e}_\theta + \frac{1}{r \sin \theta} \frac{\partial f}{\partial \varphi} \vec{e}_\varphi \\ \text{div } \vec{a} &= \frac{\partial a_r}{\partial r} + \frac{2a_r}{r} + \frac{1}{r} \frac{\partial a_\theta}{\partial \theta} + \frac{a_\theta}{r \tan \theta} + \frac{1}{r \sin \theta} \frac{\partial a_\varphi}{\partial \varphi} \\ \text{rot } \vec{a} &= \left(\frac{1}{r} \frac{\partial a_\varphi}{\partial \theta} + \frac{a_\theta}{r \tan \theta} - \frac{1}{r \sin \theta} \frac{\partial a_\theta}{\partial \varphi} \right) \vec{e}_r + \left(\frac{1}{r \sin \theta} \frac{\partial a_r}{\partial \varphi} - \frac{\partial a_\varphi}{\partial r} - \frac{a_\varphi}{r} \right) \vec{e}_\theta + \\ &\quad \left(\frac{\partial a_\theta}{\partial r} + \frac{a_\theta}{r} - \frac{1}{r} \frac{\partial a_r}{\partial \theta} \right) \vec{e}_\varphi \\ \nabla^2 f &= \frac{\partial^2 f}{\partial r^2} + \frac{2}{r} \frac{\partial f}{\partial r} + \frac{1}{r^2} \frac{\partial^2 f}{\partial \theta^2} + \frac{1}{r^2 \tan \theta} \frac{\partial f}{\partial \theta} + \frac{1}{r^2 \sin^2 \theta} \frac{\partial^2 f}{\partial \varphi^2} \end{aligned}$$

General orthonormal curvilinear coordinates (u, v, w) can be obtained from cartesian coordinates by the transformation $\vec{x} = \vec{x}(u, v, w)$. The unit vectors are then given by:

$$\vec{e}_u = \frac{1}{h_1} \frac{\partial \vec{x}}{\partial u}, \quad \vec{e}_v = \frac{1}{h_2} \frac{\partial \vec{x}}{\partial v}, \quad \vec{e}_w = \frac{1}{h_3} \frac{\partial \vec{x}}{\partial w} \quad (9.1.4.4.7)$$

where the factors h_i set the norm to 1. Then holds:

$$\begin{aligned}
 \text{grad} f &= \frac{1}{h_1} \frac{\partial f}{\partial u} \vec{e}_u + \frac{1}{h_2} \frac{\partial f}{\partial v} \vec{e}_v + \frac{1}{h_3} \frac{\partial f}{\partial w} \vec{e}_w \\
 \text{div } \vec{a} &= \frac{1}{h_1 h_2 h_3} \left(\frac{\partial}{\partial u} (h_2 h_3 a_u) + \frac{\partial}{\partial v} (h_3 h_1 a_v) + \frac{\partial}{\partial w} (h_1 h_2 a_w) \right) \\
 \text{rot } \vec{a} &= \frac{1}{h_2 h_3} \left(\frac{\partial (h_3 a_w)}{\partial v} - \frac{\partial (h_2 a_v)}{\partial w} \right) \vec{e}_u + \frac{1}{h_3 h_1} \left(\frac{\partial (h_1 a_u)}{\partial w} - \frac{\partial (h_3 a_w)}{\partial u} \right) \vec{e}_v + \\
 &\quad \frac{1}{h_1 h_2} \left(\frac{\partial (h_2 a_v)}{\partial u} - \frac{\partial (h_1 a_u)}{\partial v} \right) \vec{e}_w \\
 \nabla^2 f &= \frac{1}{h_1 h_2 h_3} \left[\frac{\partial}{\partial u} \left(\frac{h_2 h_3}{h_1} \frac{\partial f}{\partial u} \right) + \frac{\partial}{\partial v} \left(\frac{h_3 h_1}{h_2} \frac{\partial f}{\partial v} \right) + \frac{\partial}{\partial w} \left(\frac{h_1 h_2}{h_3} \frac{\partial f}{\partial w} \right) \right]
 \end{aligned}$$

This page titled [9.1.4.4: The Del-operator](#) is shared under a [CC BY](#) license and was authored, remixed, and/or curated by [Johan Wevers](#).

Index

A

Angular momentum

[9.1.1: Mechanics](#)

Apparent forces

[9.1.1: Mechanics](#)

B

Bessel function

[9.1.3: Waves](#)

C

Centre of mass

[9.1.1: Mechanics](#)

Collisions

[9.1.1: Mechanics](#)

Conservative force fields

[9.1.1: Mechanics](#)

Coordinate system

[9.1.1: Mechanics](#)

Coupled conductors

[9.1.2: Oscillations](#)

Critically damped oscillator

[9.1.2: Oscillations](#)

Cut off frequency

[9.1.3: Waves](#)

Cylindrical waves

[9.1.3: Waves](#)

D

Damping frequency (oscillator)

[9.1.2: Oscillations](#)

Del operator

[9.1.4.4: The Del-operator](#)

doppler effect

[9.1.3: Waves](#)

E

Electric oscillation

[9.1.2: Oscillations](#)

energy

[9.1.1: Mechanics](#)

F

Fixed coordinate system

[9.1.1: Mechanics](#)

force

[9.1.1: Mechanics](#)

G

Generating functions

[9.1.1: Mechanics](#)

Gravitation

[9.1.1: Mechanics](#)

Green's function

[9.1.3: Waves](#)

group velocity

[9.1.3: Waves](#)

H

Hamilton mechanics

[9.1.1: Mechanics](#)

Harmonic oscillation

[9.1.2: Oscillations](#)

I

Impedance, system

[9.1.2: Oscillations](#)

K

Kepler's orbital equations

[9.1.1: Mechanics](#)

L

Lagrange mechanics

[9.1.1: Mechanics](#)

linearization

[9.1.1: Mechanics](#)

Liouville's equations

[9.1.1: Mechanics](#)

Longitudinal waves

[9.1.3: Waves](#)

M

Mechanical oscillation

[9.1.2: Oscillations](#)

Moment of Inertia

[9.1.1: Mechanics](#)

momentum

[9.1.1: Mechanics](#)

Motion around an equilibrium

[9.1.1: Mechanics](#)

Moving coordinate system

[9.1.1: Mechanics](#)

N

Newtonian equations of motion

[9.1.1: Mechanics](#)

O

Orbital equations

[9.1.1: Mechanics](#)

P

Pendulums

[9.1.2: Oscillations](#)

phase space

[9.1.1: Mechanics](#)

phase velocity

[9.1.3: Waves](#)

Physical Constants

[9.1.4.1: Physical Constants](#)

Plane waves

[9.1.3: Waves](#)

Polar coordinates

[9.1.1: Mechanics](#)

Powers of 10

[9.1.4.2: Prefixes for Powers of 10](#)

principal axes

[9.1.1: Mechanics](#)

Q

Quality (mechanical oscillator)

[9.1.2: Oscillations](#)

R

Refractive index

[9.1.3: Waves](#)

Relative motion

[9.1.1: Mechanics](#)

Resonance curve

[9.1.2: Oscillations](#)

Resonance frequency

[9.1.2: Oscillations](#)

S

SI Units

[9.1.4: Physical Constants, Units, Del Operator](#)

spherical waves

[9.1.3: Waves](#)

spring

[9.1.2: Oscillations](#)

Stationary phase method

[9.1.3: Waves](#)

Steiner's theorem

[9.1.1: Mechanics](#)

Stiffness (oscillator)

[9.1.2: Oscillations](#)

T

TE

[9.1.3: Waves](#)

TEM

[9.1.3: Waves](#)

TM

[9.1.3: Waves](#)

Transformers, couples

[9.1.2: Oscillations](#)

transverse waves

[9.1.3: Waves](#)

V

Van der Pol equation

[9.1.3: Waves](#)

Variational Calculus

[9.1.1: Mechanics](#)

Virial theorem

[9.1.1: Mechanics](#)

W

Wave equation

[9.1.3: Waves](#)

Waveguide

[9.1.3: Waves](#)

Waves in long conductors

[9.1.2: Oscillations](#)

Glossary

Sample Word 1 | Sample Definition 1

Glossary

Sample Word 1 | Sample Definition 1

Detailed Licensing

Overview

Title: 9: A Physics Formulary

Webpages: 30

All licenses found:

- [Undeclared](#): 53.3% (16 pages)
- [CC BY 4.0](#): 46.7% (14 pages)

By Page

- 9: A Physics Formulary - [CC BY 4.0](#)
 - Front Matter - [CC BY 4.0](#)
 - [TitlePage](#) - [Undeclared](#)
 - [InfoPage](#) - [Undeclared](#)
 - [Table of Contents](#) - [Undeclared](#)
 - [Licensing](#) - [Undeclared](#)
 - 9.1: Physics Formulas (Wevers) - [CC BY 4.0](#)
 - Front Matter - [CC BY 4.0](#)
 - [TitlePage](#) - [Undeclared](#)
 - [InfoPage](#) - [Undeclared](#)
 - [Table of Contents](#) - [Undeclared](#)
 - [Licensing](#) - [Undeclared](#)
 - 9.1.1: Mechanics - [CC BY 4.0](#)
 - 9.1.2: Oscillations - [CC BY 4.0](#)
 - 9.1.3: Waves - [CC BY 4.0](#)
 - 9.1.4: Physical Constants, Units, Del Operator - [CC BY 4.0](#)
 - 9.1.4.1: Physical Constants - [CC BY 4.0](#)
 - 9.1.4.2: Prefixes for Powers of 10 - [CC BY 4.0](#)
 - 9.1.4.3: SI Units - [CC BY 4.0](#)
 - 9.1.4.4: The Del-operator - [CC BY 4.0](#)
 - Back Matter - [CC BY 4.0](#)
 - [Index](#) - [Undeclared](#)
 - [Glossary](#) - [Undeclared](#)
 - [Glossary](#) - [Undeclared](#)
 - [Detailed Licensing](#) - [Undeclared](#)
 - Back Matter - [CC BY 4.0](#)
 - [Index](#) - [Undeclared](#)
 - [Glossary](#) - [Undeclared](#)
 - [Glossary](#) - [Undeclared](#)
 - [Detailed Licensing](#) - [Undeclared](#)